

# ホイールコンベヤの選定

## 04 | 仕様一覧及び耐荷重表

種類	型式	ホイール寸法(単位mm)			フレーム断面寸法(単位mm)				形状	機高	標準フレーム全長	ホイールピッチ	ホイール1個あたりの許容荷重(kg)
		外径φ	幅	軸径φ	高	下幅	上幅	板厚					
プレス	2509PL	25.4	9	6	26	7		1.2	┌┐	30.5	1000 1500 2000	30 35	20
	2015PL	20	15	6	26	7		1.2	┌┐	27.8	1000 1500 2000	25 30 35	20
	2025PL	20	25	6	26	7		1.2	┌┐	27.8	1000 1500 2000	25 30 35	20
	3812PS	38	12	6	40	11	7	1.6	┌┐	47	1800 2000 2400 3000	50 75 100	20
	3812PM	38	12	6	40	10	7	1.6	┌┐	47	1800 2000 2400 3000	50 75 100	20
	3812PV	38	12	6	45	10	6	2	┌┐	52	1800 2000 2400 3000	50 75 100	20
	3812PL	38	12	6	49	11		2.3	┌┐	54	1800 2000 2400 3000	50 75 100	20
	4012PL	40	12	6	49	11		2.3	┌┐	55	1800 2000 2400 3000	50 75 100	20
	4020PL	40	20	6	49	11		2.3	┌┐	55	1800 2000 2400 3000	50 75 100	20
	4012PH	40	12	6	46.3	16.6	30	1.6	┌┐	54.1	1800 2000 2400 3000	50 75 100	20
	4020PH	40	20	6	46.3	16.6	30	1.6	┌┐	54.1	1800 2000 2400 3000	50 75 100	20
	4020PLW	40	20	6	49	11		2.3	┌┐	55	1800 2000 2400 3000	50 75 100	20
	5020PH	50	20	6	46.3	16.6	30	1.6	┌┐	59.1	1800 2000 2400 3000	50 75 100	20
	5020PLW	50	20	6	49	11		2.3	┌┐	60	1800 2000 2400 3000	50 75 100	20
	5020PAW	50	20	6	40	40		3	┌┐	52	2000 3000	40 50	20
3812AL	38	12	6	45	10	6	2	┌┐	52	1800 2000 2400 3000	50 75 100	20	
3812SUS	38	12	6	49	11		2	┌┐	54	1800 2000 2400 3000	50 75 100	20	
切削	2509KL	25.4	9	6	26	7		1.2	┌┐	30.5	1000 1500 2000	30 35	30
	2015KL	20	15	6	26	7		1.2	┌┐	27.8	1000 1500 2000	25 30 35	30
	2025KL	20	25	6	26	7		1.2	┌┐	27.8	1000 1500 2000	25 30 35	30
	2523KL	25	23	8	25	9		1.6	┌┐	29.5	1000 1500 2000	30 35	50
	3225KL	32	25	8	35	13		3.2	┌┐	40	1000 1500 2000 3000	40 60 100	90
	3609KL	36	9	6	49	11		2.3	┌┐	53	1800 2000 2400 3000	50 75 100	40
	3609KC	36	9	6	42.3	21	10	2.3	┌┐	47.3	1800 2000 2400 3000	50 75 100	40
	3609KH	36	9	6	46.3	16.6	30	1.6	┌┐	52.1	1800 2000 2400 3000	50 75 100	40
	3609KAW	36	9	6	40	40		3	┌┐	45	2000 3000	30 40 50	40
	5013K	50	13	12	60	25	15	2.3	┌┐	65	1800 2000 2400 3000	75 100 150	100
	5013KAW	50	13	12	50	50		6	┌┐	60	2000 3000	40 50	100
3050KL	30	50	10	30	30		4.5	┌┐	37	1000 2000 3000	35 50 70	160	
樹脂	2607JL	26	7	6	26	7		1.2	┌┐	30.8	1000 1500 2000	30 35	20
	3812JS	38	12	6	40	11	7	1.6	┌┐	47	1800 2000 2400 3000	50 75 100	15
	3812JV	38	12	6	45	10	6	2	┌┐	52	1800 2000 2400 3000	50 75 100	15
	4020JL	40	20	6	49	11		2.3	┌┐	55	1800 2000 2400 3000	50 75 100	15
	3612JH	36	12	6	46.3	16.6	30	1.6	┌┐	52.1	1800 2000 2400 3000	50 75 100	15
	4012JH	40	12	6	46.3	16.6	30	1.6	┌┐	54.1	1800 2000 2400 3000	50 75 100	15
	4617JH	46	17	6	46.3	16.6	30	1.6	┌┐	57.1	1800 2000 2400 3000	50 75 100	18
	5016JH	50	16	6	46.3	16.6	30	1.6	┌┐	59.1	1800 2000 2400 3000	50 75 100	18
5020JH	50	20	6	46.3	16.6	30	1.6	┌┐	59.1	1800 2000 2400 3000	50 75 100	18	
ゴム	4009GS	40	9	6	40	11	7	1.6	┌┐	48	1800 2000 2400 3000	50 75 100	30
	4009GV	40	9	6	45	10	6	2	┌┐	53	1800 2000 2400 3000	50 75 100	30
	4009GL	40	9	6	49	11		2.3	┌┐	55	1800 2000 2400 3000	50 75 100	30
	4009GC	40	9	6	42.3	21	10	2.3	┌┐	49.3	1800 2000 2400 3000	50 75 100	30
	4009GH	40	9	6	46.3	16.6	30	1.6	┌┐	54.1	1800 2000 2400 3000	50 75 100	30
ピッキング	3620UP	36	20	3.2	32	40		1	㊦	46	1000 1500 1800 2000 2400 2500 3000	40 50	10
	3620UD	36	20	3.2	32	40		1	㊦	46	1000 1500 1800 2000 2400 2500 3000	40 50	10
	3620US	36	20	3.2	32	40		1	㊦	46	1000 1500 1800 2000 2400 2500 3000	40 50	15
	3620SB	36	20	3.2	32	40		1	㊦	46	1000 1500 1800 2000 2400 2500 3000	40 50	15
	1820UP	18	20	3.2	32	40		1	㊦	37	1000 1500 2000 3000	20 25	10
	1820UD	18	20	3.2	32	40		1	㊦	37	1000 1500 2000 3000	20 25	10
	3822UPF	22	20	3.2	32	40		1	㊦	47	1000 1500 1800 2000 2400 2500 3000	40 50	10
	1820ECON	18	20	3.2	32	40		1	㊦	37	1000 1800 2000 2400 3000	20 25	10
	1820ECON-D	18	20	3.2	32	40		1	㊦	37	1000 1800 2000 2400 3000	20 25	10
	3620ECON	36	20	3.2	32	40		1	㊦	46	1000 1800 2000 2400 3000	40 50	10
	3620ECON-D	36	20	3.2	32	40		1	㊦	46	1000 1800 2000 2400 3000	40 50	10
	3620ECON-S	36	20	3.2	32	40		1	㊦	46	1000 1800 2000 2400 3000	40 50	15
	3670UP	36	67	3.2	36	87		1	㊦	48	1000 1500 1800 2000 2400 2500 3000	40 50	10
	3670UD	36	67	3.2	36	87		1	㊦	48	1000 1500 1800 2000 2400 2500 3000	40 50	10
1870UP	18	67	3.2	36	87		1	㊦	39	1000 1500 2000 3000	20 25	10	
1870UD	18	67	3.2	36	87		1	㊦	39	1000 1500 2000 3000	20 25	10	

ローラコンベヤ

ホイールコンベヤ

伸縮ローラコンベヤ

モーターローラコンベヤ

駆動ローラコンベヤ

エアリー式昇降装置(サンアツ)